


coding style table	
	style A: for connectors 6-pole
	style B: for connectors from 10 to 14-pole
	style C: for connectors from 16 to 64-pole

full range of P/N's and dimensions shown on page 2/2

further information see product data sheet

	All rights reserved Department EL PD	Created by TADJE	Inspected by STORCK	Standardisation HOFFMANN	Date 2020-05-05	State Final Release	Ref. Sub.
	HARTING Electronics GmbH D-32339 Espelkamp	Title SEK 18 female conn with closed end cover strain relief			Doc-Key / ECM-Nr. 100662934/UGD/009/C 500000172195		Rev. C
		Type TB	Number 09185XXX814		Page 1/2		

no. of contacts	performance level			insulator colour	dimensions				
	PL3	PL2	S4 (NM30)		A max.	B	C	D	
06	09 18 506 7814	09 18 506 6814	09 18 506 5814	grey	12,2	2 x 2,54 (=5,08)	2	7,62	
10	09 18 510 7814	09 18 510 6814	09 18 510 5814		17,3	4 x 2,54 (=10,16)	3,8	12,7	
14	09 18 514 7814	09 18 514 6814	09 18 514 5814		22,4	6 x 2,54 (=15,24)	3,8	17,78	
16	09 18 516 7814	09 18 516 6814	09 18 516 5814		24,9	7 x 2,54 (=17,78)	3,8	20,32	
20	09 18 520 7814	09 18 520 6814	09 18 520 5814		30	9 x 2,54 (=22,86)	3,8	25,4	
26	09 18 526 7814	09 18 526 6814	09 18 526 5814		37,6	12 x 2,54 (=30,48)	3,8	33,02	
30	09 18 530 7814	09 18 530 6814	09 18 530 5814		42,7	14 x 2,54 (=35,56)	3,8	38,5	
34	09 18 534 7814	09 18 534 6814	09 18 534 5814		47,8	16 x 2,54 (=40,64)	3,8	43,18	
40	09 18 540 7814	09 18 540 6814	09 18 540 5814		55,4	19 x 2,54 (=48,26)	3,8	50,8	
50	09 18 550 7814	09 18 550 6814	09 18 550 5814		68,1	24 x 2,54 (=60,96)	3,8	63,5	
60	09 18 560 7814	09 18 560 6814	09 18 560 5814		80,8	29 x 2,54 (=73,66)	3,8	76,6	
64	09 18 564 7814	09 18 564 6814	09 18 564 5814		85,9	31 x 2,54 (=78,74)	3,8	81,28	
06	09 18 506 7814 001	09 18 506 6814 001	09 18 506 5814 001		black	12,2	2 x 2,54 (=5,08)	2	7,62
10	09 18 510 7814 001	09 18 510 6814 001	09 18 510 5814 001			17,3	4 x 2,54 (=10,16)	3,8	12,7
14	09 18 514 7814 001	09 18 514 6814 001	09 18 514 5814 001	22,4		6 x 2,54 (=15,24)	3,8	17,78	
16	09 18 516 7814 001	09 18 516 6814 001	09 18 516 5814 001	24,9		7 x 2,54 (=17,78)	3,8	20,32	
20	09 18 520 7814 001	09 18 520 6814 001	09 18 520 5814 001	30		9 x 2,54 (=22,86)	3,8	25,4	
26	09 18 526 7814 001	09 18 526 6814 001	09 18 526 5814 001	37,6		12 x 2,54 (=30,48)	3,8	33,02	
30	09 18 530 7814 001	09 18 530 6814 001	09 18 530 5814 001	42,7		14 x 2,54 (=35,56)	3,8	38,5	
34	09 18 534 7814 001	09 18 534 6814 001	09 18 534 5814 001	47,8		16 x 2,54 (=40,64)	3,8	43,18	
40	09 18 540 7814 001	09 18 540 6814 001	09 18 540 5814 001	55,4		19 x 2,54 (=48,26)	3,8	50,8	
50	09 18 550 7814 001	09 18 550 6814 001	09 18 550 5814 001	68,1		24 x 2,54 (=60,96)	3,8	63,5	
60	09 18 560 7814 001	09 18 560 6814 001	09 18 560 5814 001	80,8		29 x 2,54 (=73,66)	3,8	76,6	
64	09 18 564 7814 001	09 18 564 6814 001	09 18 564 5814 001	85,9		31 x 2,54 (=78,74)	3,8	81,28	

	All rights reserved	Created by TADJE	Inspected by STORCK	Standardisation HOFFMANN	Date 2020-05-05	State Final Release
	Department EL PD	Title SEK 18 female conn with closed end cover strain relief				Doc-Key / ECM-Nr. 100662934/UGD/009/C 500000172195
HARTING Electronics GmbH D-32339 Espelkamp		Type TB	Number 09185XXX814		Rev. C	Page 2/2