



| | Crimping inner conductor | Crimping outer conductor |
|--------------|--------------------------|--------------------------|
| Hand tool | 09 99 000 0501 | 09 99 000 0503 |
| Locator | 09 99 000 0507 | 09 99 000 0508 |
| Cables | RG174U, RG188AU, RG316U | |
| Cavity | | B |
| Tool setting | Conductor cross-section | Selection |
| | AWG 24 | SEL 5 |
| | AWG 26 | SEL 5 |
| | AWG 28 | SEL 4 |
| | AWG 30 | SEL 3 |

| | | | |
|---------------|------------------|----------------------|----------------------|
| 0969 282 7140 | Mating area | 0,2 μm Au | 0,2 μm Au |
| | Termination area | 5 μm Sn | 0,2 μm Au |
| 0969 282 5140 | Mating area | 0,8 μm Au | 1,3 μm Au |
| | Termination area | 0,2 μm Au | 1,3 μm Au |
| Part number | Plating | outer conductor | inner conductor |

| | | | | | | | |
|---|-----------------------|---|--------------|-----------------|------------|--|--|
| | All rights reserved | Created by | Inspected by | Standardisation | Date | State | |
| | Department EC PD - CN | ZHUANGJ | LUOK | HOFFMANN | 2017-01-25 | Final Release | |
| HARTING Electronics GmbH D-32339 Espelkamp | | Title male coaxial contact 50 Ohm straight cable termination | | | | Doc-Key / ECM-Nr. 100706793/UGD/000/A 500000114200 | |
| | | Type | Number | | Rev. | Page | |
| | | TB | 0969282X140 | | A | 1/1 | |