


1 2 3 4 5 6

MALE END VIEW




- 1. BN
- 2. BU
- 3. WH
- 4. GN/YE
- 5. OG
- 6. YE
- 7. GY
- 8. PK
- 9. RD
- 10. BN/WH
- 11. BU/WH
- 12. GN/WH

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	PBT/WHITE	
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK	
CONTACT MATERIAL/COLOR	BRASS/GOLD	
COUPLING NUT MATERIAL/PLATING	ZINC ALLOY/NICKEL	
RATED CURRENT	6 A	
RATED VOLTAGE	300 V	
OUTER CABLR JACKET MATERIAL/COLOR	PVC/BLACK	PUR/BLACK
CONDUCTOR INSULATION MATERIAL	PVC	
NUMBER OF CONDUCTORS (AWG)	12×18AWG	
OPERATING TEMPERATURE	-40°C — +80°C	
PROTECTION CLASS	IEC IP67	

HARTING P/N	Type of cable	Cable length(mm)
21373400C70050	PUR	5000 ⁺²⁰⁰ ₋₀
21373400C70100	PUR	10000 ⁺⁴⁰⁰ ₋₀
21373400C71050	PVC	5000 ⁺²⁰⁰ ₋₀
21373400C71100	PVC	10000 ⁺⁴⁰⁰ ₋₀



	All rights reserved Department HCS - CN	Tech. Character.		Free size tol.		According to production drawing	
Created by LINI		Inspected by LIANL		Standardisation LIANL		Date 2021-08-31	
State Final release		Title M23_12P MA,Int-thread,ANG PVC/PUR cable,xxM					
Doc-Key / ECM-Nr. /		Type TB		Number 2137 34 00 C 7X XXX		Rev. B	

Rev.	Description	Appr.	Date
B	Revised stripping tolerance (ECN21405)	Ivy Lin	08/31/21
A	First issue.	Lucy Zheng	06/25/19

HARTING Customised Solutions
D-32339 Espelkamp