



HAR-FLEX 40P Female With Strain Relief

HAR-FLEX 40P Female With Strain Relief

WIRING TABLE

C1	WIRE	C2
1	AWG30	1
2	AWG30	2
3	AWG30	3
-	AWG30	-
39	AWG30	39
40	AWG30	40

HARTING P/N & REV	LENGTH ( L )
3315 244 100 0044 . 00	100 ± 3
3315 244 150 0045 . 00	150 ± 3
3315 244 200 0045 . 00	200 ± 3

- NOTES:
- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT(500VDC)TEST.
  - 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
  - 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON(QTY ACCORDING TO ACTUAL CONDITION)
  - 4.)WHITE LABEL CONTENT:

DATA CODE  
HARTING P/N

	All rights reserved	Created by	Inspected by	Standardisation	Date	State
	Department HCS - CN	ZHENGL	LIK	LIK	2017-09-25	Final Release
HARTING Customised Solutions D-32427 Minden		Title Har-flex 40Pole,dul-end,with SR,L=XX MM			Doc-Key / ECM-Nr. 100737151/UGD/001/A 500000125756	
		Type	Number	Rev.	Page	
		TB	33150009	A	1/1	