



HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

HAR-FLEX 26 POLE FEMALE CONNECTOR WITH STRAIN RELIEF

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
-	AWG 30	-
25	AWG 30	25
26	AWG 30	26

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY THE PLASTIC BAG,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION) EXPORT CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY.
- 4.)WHITE LABEL CONTENT:

DATA CODE&LOT INFORMATION
HARTING P/N&REVISION

	All Dimensions in mm Original Size DIN A3		Scale 2:1	Free size tol. \		Ref. \
	All rights reserved Department HCS - CN		Created by ZHENGL	Inspected by WANGE	Standardisation CHENJU	Date 2018-10-15
HARTING Customised Solutions D-32339 Espelkamp		Title Har-flex 26 p double ends with SR, 0.3m			State Final Release	
		Type TB	Number 33 15 243 0300066		Doc-Key / ECM-Nr. 100806875/UGD/000/A 50000014.1278	Page 1/1
				Rev. A		