



Hybrid Han 3A - LC Duplex and Power DC, with metal housing

Hybrid outdoor cable 2xFO Singlemode + 3x2.5sqmm

Loading-Plan (Power DC version)

Shield (not connected)

- A — Orange
- B — Blue
- 1 — Black
- 2 — Blue
- PE — Green-Yellow

- Protection level: IP65/IP67
 - Temperature range: -40°C ... +70°C

9	335711130050034	Hybrid cable 2xFO - 3x2.5/3.5	300
8	33571111005004		100
7	33571110605004		60
6	33571110505004		50
5	33571110405004		40
4	33571110205004		20
3	33571110105004		10
2	33571110055004		5
1	33571110015004		1
Cont No.	Part-No.	Type of cable	Dim.a

All rights reserved Department EC PD - RO		All Dimensions in mm Original Size DIN A3	Scale 2:1	Free size tol.	Ref. Sub.
HARTING Electronics GmbH D-32339 Espelkamp		Created by POPESCU	Inspected by AVRAM	Standardisation HOFFMANN	Date 2015-12-18
Title Han 3A FO Hybrid Cable Assembly		Type TB		State Final Release	
Number 3357111XXX5004		Doc-Key / ECM-Nr. 100643664/UGD/037/A 50000098235		Rev. A	Page 1/1