



1 For strain relief an additional InduCom cable clamp or a crimp flange and ferrule combination depending on the cable is necessary

Content InduCom hood			Spare parts (MOQ100)	
Pos.	Quantity	Description	Part Number	Quantity
01	1	metal hood		
02	1	metal cover		
03	1	blank piece (not assembled)	6103 000 0042	1
04	2	locking screw (assembled):		
		either knurled thumb screws 4-40 UNC (for 0110)	0967 002 9018	1
		or hexagonal M3 with captive washer (for 1110)	0967 002 9019	1
		or hexagonal 4-40 UNC with captive washer (for 2110)	0967 002 9020	1
		or knurled thumb screws M3 (for 3110)	0967 002 9017	1
05	1	grounding screw (not assembled) for version with internal grounding block	0963 002 0007	1
06	3	cover screw M2,5 with philips head (not losable in cover) max. torque=0,3Nm	0963 002 0006	1

Part Number	Dim. B screw size	Screw type	Identification for locking screw	Internal grounding block
6103 001 Y110 ZZZ				
6103 001 0110	4-40 UNC	Knurled thumb screw	Without ring	With internal grounding block
6103 001 1110	M3	Hexagonal screw with captive washer	1 & Knurled head	
6103 001 2110	4-40 UNC	Hexagonal screw with captive washer	3	
6103 001 3110	M3	Knurled thumb screw	With ring	Without internal grounding block
6103 001 0110 010	4-40 UNC	Knurled thumb screw	Without ring	
6103 001 1110 010	M3	Hexagonal screw with captive washer	1 & Knurled head	
6103 001 2110 010	4-40 UNC	Hexagonal screw with captive washer	3	
6103 001 3110 010	M3	Knurled thumb screw	With ring	

All rights reserved  
 Department EL PD  
 HARTING D-32339 Espelkamp

All Dimensions in mm Original Size DIN A3  
 Scale 1:1  
 Free size tol.

Created by ZENGDO  
 Inspected by LUOK  
 Standardisation ROEBEN  
 Date 2022-01-05  
 State Final Release

Title InduCom size 1 (9-pole) easy access hood assembly  
 Type TB  
 Number 6103001Y110

Ref. Sub.  
 Doc-Key / ECM-Nr. 100888108/UGD/003/A 50000208892  
 Rev. A  
 Page 1/1