

## SEK-19 SV HT MA STD ANG29 RLG 16P PL2




Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 19 516 6903  |
| Specification      | SEK-19 SV HT MA STD ANG29 RLG 16P PL2   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09195166903">https://b2b.harting.com/09195166903</a> |

### Identification

|                            |                |
|----------------------------|----------------|
| Category                   | Connectors     |
| Series                     | SEK Standard   |
| Element                    | Male connector |
| Description of the contact | Angled         |

### Version

|                    |                                    |
|--------------------|------------------------------------|
| Termination method | Reflow soldering termination (THR) |
| Locking type       | With long levers                   |
| Connection type    | PCB to cable                       |
| Number of contacts | 16                                 |
| Termination length | 2.9 mm                             |
| Performance level  | 2                                  |

### Technical characteristics

|                                    |   |
|------------------------------------|---|
| Contact rows                       | 2   |
| Contact spacing (termination side) | 2.54 mm   |
| Rated current                      | 1 A   |
| Insulation resistance              | $>10^9 \Omega$  |
| Contact resistance                 | $\leq 20 \text{ m}\Omega$                                       |
| Limiting temperature               | -55 ... +125 °C (during reflow soldering max. +240 °C for 60 s) |
| Insertion and withdrawal force     | $\leq 32 \text{ N}$   |
| Mating cycles                      | $\geq 250$  |
| Test voltage $U_{r.m.s.}$          | 1 kV  |



Pushing Performance

## Technical characteristics

Isolation group II (400 ≤ CTI < 600)

## Material properties

|   |  |
|---|--|
| Material (insert)                         | Thermoplastic resin (PCT)                                |
| Colour (insert)                           | Beige  |
| Material (contacts)                       | Copper alloy   |
| Surface (contacts)                        | Sn over Ni Termination side<br>Au over Pd/Ni Mating side |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant  |
| ELV status                                | compliant  |
| China RoHS                                | e  |
| REACH Annex XVII substances               | No   |
| REACH ANNEX XIV substances                | No   |
| REACH SVHC substances                     | No   |

## Specifications and approvals


|                |  |
|----------------|--|
| Specifications | IEC 60603-13   |
| UL / CSA       | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079 |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 100                                      |
| Net weight                     | 5 g                                      |
| Country of origin              | Romania                                  |
| European customs tariff number | 85366990                                 |
| eCl@ss                         | 27460201 PCB connector (board connector) |

### Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.  
 Measuring and testing techniques acc. to IEC 60512-5-2



- ① Temperature raise
- ② Derating curve
- ③ Derating curve 80%

### Cross section of solder termination

