

har-SAB M12/8/5p PAC 5m PVC w/o LED



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 07 001 2225 100 |
| Specification | har-SAB M12/8/5p PAC 5m PVC w/o LED |
| HARTING eCatalogue | https://b2b.harting.com/09070012225100 |

Identification

| | |
|---------------|---------------------------------|
| Series | Circular connectors M12 |
| Element | Distribution boxes |
| Specification | Pre-assembled termination shell |

Version

| | |
|-----------------------|------------------------|
| Cable length | 5 m |
| Core structure | 3x AWG 18 + 16x AWG 22 |
| Total number of ports | 8 |
| Number of contacts | 5 |

Technical characteristics

| | |
|--|--------------------|
| Rated current | 9 A |
| Rated voltage | 10 V DC 30 V DC |
| Limiting temperature | -30 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP67 |
| Number of channels per port | 2 |
| Circuit logic | PNP |

Material properties

| | |
|------------------|-----|
| Material (cable) | PVC |
|------------------|-----|



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------|---|
| UL / CSA | UL 2238 CYJV.E500416 CSA-C22.2 CYJV7.E500416 |
|----------|---|

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Country of origin | China |
| European customs tariff number | 85444290 |
| GTIN | 5713140277359 |
| eCl@ss | 27440108 Passive Sensor-Actuator-Interface (with cable) |