

Han TC70-HMC-MC-CRT-6 mm²-AU

		Part number	09 11 200 6130
		Specification	Han TC70-HMC-MC-CRT-6 mm ² -AU
		HARTING eCatalogue	https://b2b.harting.com/09112006130
Identification			
Category	Contacts		
Series	TC 70		
Type of contact	Crimp conta	ict	
Features	lead-free		
Version			
Gender	Male		
Manufacturing process	Turned cont	acts	
Technical characteristics			
Conductor cross-section	6 mm²		
Operating current	≤70 A		
Contact resistance	≤0.3 mΩ		
Stripping length	15 mm		
Limiting temperature	-40 +125	°C	
Mating cycles with other HMC components	≥10,000		

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	HMC gold plated

Page 1 / 2 | Creation date 2022-10-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 11 200 6130 Han TC70-HMC-MC-CRT-6 mm²-AU



Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Commercial data	
Packaging size	10
Net weight	8.9 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140188129
eCl@ss	27440204 Contact for industrial connectors