




Pushing Performance
Since 1945

Han TC100-HMC-FC-CRT-25 mm²-AU



| | |
|--------------------|---|
| Part number | 09 11 200 6225 |
| Specification | Han TC100-HMC-FC-CRT-25 mm ² -AU |
| HARTING eCatalogue | https://b2b.harting.com/09112006225 |

Identification

| | |
|-----------------|---------------|
| Category | Contacts |
| Series | TC 100 |
| Type of contact | Crimp contact |
| Features | lead-free |

Version

| | |
|-----------------------|-----------------|
| Gender | Female |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|---|--------------------|
| Conductor cross-section | 25 mm ² |
| Operating current | ≤100 A |
| Contact resistance | ≤0.3 mΩ |
| Stripping length | 19 mm |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles with other HMC components | ≥10,000 |

Material properties

| | |
|---------------------|-----------------|
| Material (contacts) | Copper alloy |
| Surface (contacts) | HMC gold plated |



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------------|--------------------------|
| Specifications | IEC 60664-1 IEC 61984 |
|----------------|--------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 15.1 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140188297 |
| eCl@ss | 27440204 Contact for industrial connectors |