

Pneumatic contact male 1,6 mm



| Part number | 09 14 000 6151 |
|--------------------|-------------------------------------|
| Specification | Pneumatic contact male 1,6 mm |
| HARTING eCatalogue | https://b2b.harting.com/09140006151 |

Image is for illustration purposes only. Please refer to product description.

Identification

REACH ANNEX XIV substances

| Category | Contacts |
|-----------------------------|------------------------------|
| Type of contact | Pneumatic contact |
| Description of the contact | Without shut-off Straight |
| Version | |
| Gender | Male |
| Manufacturing process | Turned contacts |
| Technical characteristics | |
| Limiting temperature | -40 +80 °C |
| Operating pressure | ≤8 bar |
| Tube inner diameter | 1.6 mm |
| Material properties | |
| Material (contacts) | Delrin acetal |
| Material (seal) | Buna-N |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| | |

Page 1 / 2 | Creation date 2022-08-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Not contained



| Material properties | |
|--------------------------------|--|
| REACH SVHC substances | Not contained |
| | |
| Specifications and approvals | |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Commercial data | |
| Packaging size | 10 |
| Net weight | 0.5 g |
| Country of origin | Germany |
| European customs tariff number | 39269097 |
| GTIN | 5713140018266 |
| eCl@ss | 27440204 Contact for industrial connectors |