

Han shielded module basic, female



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 027 3121
Specification	Han shielded module basic, female
HARTING eCatalogue	https://b2b.harting.com/09140273121

Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® Shielded module basic
Size of the module	Single module
Description of the module	With 180° shielding element

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	27
further contacts	+ shielding
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.09 ... 0.52 mm ²
Rated current	4 A
Rated voltage	32 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500



Pushing Performance
Since 1945

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

Commercial data

Packaging size	2
Net weight	0.01 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140185005
eCl@ss	27440218 Module for industrial connectors (data)