

Han PushPull Power L Genderchanger



Part number	09 35 431 0501
Specification	Han PushPull Power L Genderchanger
HARTING eCatalogue	https://b2b.harting.com/09354310501

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Han [®] PushPull (V14)
Identification	Power L
Element	Gender changer
Specification	AIDA compliant
Features	Intuitive locking mechanism

Version

Shielding	Unshielded
Number of contacts	5
Fixing	Wall mountable with 4 screws type M5
Locking type	PushPull
Pack contents	incl. housing and PCB with 2x male insert

Technical characteristics

Conductor cross-section	AWG 18 AWG 13
Rated current	16 A
Rated voltage	24 V
Stripping length	10 mm Conductors 44 mm cable jacket
Tightening torque	3 Nm
Limiting temperature	-20 +50 °C
Mating cycles	≥500



Technical characteristics

Degree of protection acc. to IEC 60529

IP65 mated condition
IP67 mated condition

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side Sn over Ni Termination side
Material (hood/housing)	Aluminium
Surface (hood/housing)	Anodised
Material (seal)	NBR
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel Naphthalene

Specifications and approvals

Specifications	IEC/PAS 61076-3-126
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 UL 1059 XCFR2.E314677 CSA-C22.2 No. 158-10 XCFR8.E314677
PROFINET	Yes

Commercial data

Packaging size	1
Net weight	229.5 g
Country of origin	Germany
European customs tariff number	85366990

Product data sheet 09 35 431 0501 Han PushPull Power L Genderchanger



Commercial data

GTIN	5713140054547
eCl@ss	27440190 Industry connector (unspecified)