

Han3A RJ45 Hybrid 10G Cat6 plug 8+4p IDC



	Part number	09 45 115 1760
	Specification	Han3A RJ45 Hybrid 10G Cat6 plug 8+4p IDC
	HARTING eCatalogue	https://b2b.harting.com/09451151760

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Cable connector
Type of hood/housing	Hood
Description of hood/housing	Straight

Version

Termination method	IDC termination
Size	Han [®] 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Number of data contacts	8
Number of power contacts	4
further contacts	4x 48 V

Technical characteristics

Conductor cross-section	0.1 0.32 mm²
Conductor cross-section	AWG 27/7 AWG 22/7 Stranded AWG 27/1 AWG 22/1 Solid
Transmission characteristics	Cat. 6 Class E _A up to 500 MHz

Page 1 / 3 | Creation date 2023-01-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s	
Limiting temperature	-40 +70 °C	
Mating cycles	≥500	
Cable diameter	6 12 mm	
Vibration resistance	10-500 Hz, 5 g, 0.35 mm, 2h/axis 7.9 m/s² acc. to IEC 61373 Category 1 Class B	
Shock resistance	5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B $$	
Material properties		
Material (hood/housing)	Zinc die-cast	
Surface (hood/housing)	Powder-coated	
Colour (hood/housing)	Grey	
RoHS	compliant with exemption	
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight	
ELV status	compliant with exemption	
China RoHS	50	
REACH Annex XVII substances	Not contained	
REACH ANNEX XIV substances	Not contained	
REACH SVHC substances	Yes	
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead	
California Proposition 65 substances	Yes	
California Proposition 65 substances	Antimony trioxide Lead Nickel Naphthalene	

Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

Page 2 / 3 | Creation date 2023-01-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Commercial data

Packaging size	1
Net weight	126.42 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140058859
eCl@ss	27440113 Rectangular connectors (set)

Page 3 / 3 | Creation date 2023-01-13 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany