

# Han3A RJ45 Hybrid Cat5 plug 4+4p IDC



Part number	09 45 125 1300
Specification	Han3A RJ45 Hybrid Cat5 plug 4+4p IDC
HARTING eCatalogue	https://b2b.harting.com/09451251300

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Cable connector
Type of hood/housing	Hood
Description of hood/housing	Straight

#### Version

Termination method	IDC termination
Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8
Number of data contacts	4
Number of power contacts	4
further contacts	4x 48 V

### Technical characteristics

Conductor cross-section	0.22 0.32 mm² Stranded 0.26 0.32 mm² Solid
Conductor cross-section	AWG 24 AWG 22 Stranded AWG 23 AWG 22 Solid
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s
Limiting temperature	-40 +70 °C



#### Technical characteristics

Mating cycles	≥500
Cable diameter	6 12 mm

## Material properties

Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	Black
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel Naphthalene
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	EN 45545-2
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

#### Commercial data

Packaging size	1
Net weight	69.1 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140058880

Product data sheet 09 45 125 1300 Han3A RJ45 Hybrid Cat5 plug 4+4p IDC



#### Commercial data

eCl@ss

27440113 Rectangular connectors (set)