

HARTING F+B Hybridcable, PO 50m




Image is for illustration purposes only. Please refer to product description.

Part number	09 45 600 0335
Specification	HARTING F+B Hybridcable, PO 50m
HARTING eCatalogue	https://b2b.harting.com/09456000335

Identification

Category	System cabling
Element	Bulk cables
Specification	Not assembled
Type of cable	Hybrid cable (copper/copper)

Version

Cable length	50 m
Number of cores	13
Core structure	2x 2x AWG 22
	2x 0.75 mm ²
	2x 1.5 mm ²
	5G 2.5 mm ²

Technical characteristics

Transmission characteristics	Cat. 5e Class D up to 100 MHz
Data rate	10 Mbit/s
	100 Mbit/s
Limiting temperature	-40 ... +90 °C
Minimum bending radius	10x Cable diameter (repeated bending)

Material properties

Material (cable)	Polyolefin copolymer
Colour (cable)	Black



Pushing Performance
Since 1945

Specifications and approvals

Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topax 66
	Ecolab Topax 990
	Ecolab Topactive OKTO

Commercial data

Packaging size	1
Net weight	391 g/m
Country of origin	Germany
European customs tariff number	85444995
GTIN	5713140273993
eCl@ss	27060501 Hybrid cable