

## 15p STR FE PL3\_M3 SL\_Reel\_140 pcs



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 55 215 7621 741  |
| Specification      | 15p STR FE PL3_M3 SL_Reel_140 pcs   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09552157621741">https://b2b.harting.com/09552157621741</a> |

### Identification

|                            |                     |
|----------------------------|---------------------|
| Category                   | Connectors          |
| Series                     | D-Sub               |
| Identification             | Standard            |
| Element                    | Connector           |
| Description of the contact | Stamped<br>Straight |

### Version

|                    |  |
|--------------------|--|
| Termination method | Reflow soldering termination (SMT)       |
| Gender             | Female                                   |
| Size               | D-Sub 2                                  |
| Connection type    | Motherboard to daughtercard<br>Mezzanine |
| Number of contacts | 15                                       |
| Locking type       | Fixing flange with fitted screw lock M3  |
| Pack contents      | 140 pieces on reel                       |

### Technical characteristics

|                                    |                         |
|------------------------------------|-------------------------|
| Contact spacing (termination side) | 2.74 mm                 |
| Rated current                      | 5 A                     |
| Clearance distance                 | ≥1 mm                   |
| Creepage distance                  | ≥1 mm                   |
| Insulation resistance              | > 5 x 10 <sup>9</sup> Ω |
| Contact resistance                 | ≤25 mΩ                  |



Pushing Performance  
 Since 1945

## Technical characteristics

|                                  |   |
|----------------------------------|---|
| Tightening torque                | ≤0.4 Nm Locking screw   |
| Limiting temperature             | -55 ... +125 °C (during reflow soldering max. +240 °C for 30 s) |
| Insertion force                  | ≤50 N   |
| Withdrawal force                 | ≥4.5 N<br>≤33 N   |
| Performance level                | 3   |
| Mating cycles                    | ≥50   |
| Test voltage $U_{r.m.s.}$        | 1 kV  |
| Isolation group                  | IIIa (175 ≤ CTI < 400)  |
| PCB thickness                    | ≥1.6 mm   |
| Installation height              | 6.35 mm   |
| Hot plugging                     | No  |
| Moisture Sensitivity Level (MSL) | 1 acc. to ECA/IPC/JEDEC J-STD-020D                              |
| Process Sensitivity Level (PSL)  | R0 acc. to ECA/IPC/JEDEC J-STD-020D                             |

## Material properties

|   |   |
|---|---|
| Material (insert)                         | Liquid crystal polymer (LCP)<br>Shell: steel, nickel plated |
| Colour (insert)                           | Black   |
| Material (contacts)                       | Copper alloy  |
| Surface (contacts)                        | Noble metal over Ni   |
| Material flammability class acc. to UL 94 | V-0   |
| RoHS                                      | compliant   |
| ELV status                                | compliant   |
| China RoHS                                | e   |
| REACH Annex XVII substances               | Not contained   |
| REACH ANNEX XIV substances                | Not contained   |
| REACH SVHC substances                     | Not contained   |
| California Proposition 65 substances      | Yes   |
| California Proposition 65 substances      | Lead<br>Nickel<br>Naphthalene                               |

## Specifications and approvals

|                |           |
|----------------|-----------|
| Specifications | DIN 41652 |
|----------------|-----------|



**Pushing Performance**  
Since 1945

## Specifications and approvals

|          |  |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079 |
|----------|--|

## Commercial data

|                                |                        |
|--------------------------------|------------------------|
| Packaging size                 | 1                      |
| Net weight                     | 1,600 g                |
| Country of origin              | China                  |
| European customs tariff number | 85366990               |
| GTIN                           | 5713140069305          |
| eCl@ss                         | 27440214 D-Sub coupler |