

37p STR FE PL2_4-40 SL_Reel_140 pcs



Part number	09 55 415 6622 741
Specification	37p STR FE PL2_4-40 SL_Reel_140 pcs
HARTING eCatalogue	https://b2b.harting.com/09554156622741

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	D-Sub
Identification	Standard
Element	Connector
Description of the contact	Stamped Straight

Version

Termination method	Reflow soldering termination (SMT)
Gender	Female
Size	D-Sub 4
Connection type	Motherboard to daughtercard Mezzanine
Number of contacts	37
Locking type	Fixing flange with fitted screw lock 4-40 UNC
Pack contents	140 pieces on reel

Technical characteristics

Contact spacing (termination side)	2.76 mm
Rated current	5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	> 5 x 10 ⁹ Ω
Contact resistance	≤25 mΩ

Page 1 / 3 | Creation date 2022-12-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Technical characteristics

≤0.4 Nm Locking screw
-55 +125 °C (during reflow soldering max. +240 °C for 30 s)
≤123 N
≥11 N ≤82 N
2 acc. to CECC 75301-802
≥250
1 kV
IIIa (175 ≤ CTI < 400)
≥1.6 mm
6.35 mm
No
1 acc. to ECA/IPC/JEDEC J-STD-020D
R0 acc. to ECA/IPC/JEDEC J-STD-020D

Material properties

Colour (insert) Material (contacts) Copper alloy Surface (contacts) Noble metal over Ni Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status China RoHS e REACH Annex XVII substances Not contained	Material (insert)	Liquid crystal polymer (LCP) Shell: steel, nickel plated
Surface (contacts) Noble metal over Ni Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status China RoHS e	Colour (insert)	Black
Material flammability class acc. to UL 94 V-0 RoHS compliant ELV status compliant China RoHS e	Material (contacts)	Copper alloy
RoHS compliant ELV status compliant China RoHS e	Surface (contacts)	Noble metal over Ni
ELV status compliant China RoHS e	Material flammability class acc. to UL 94	V-0
China RoHS e	RoHS	compliant
	ELV status	compliant
REACH Annex XVII substances Not contained	China RoHS	е
	REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances Not contained	REACH ANNEX XIV substances	Not contained
REACH SVHC substances Not contained	REACH SVHC substances	Not contained
California Proposition 65 substances Not contained	California Proposition 65 substances	Not contained

Specifications DIN 41652

Specifications and approvals



Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079
OL / CSA	CSA-C22.2 No. 182.3 ECBT8.E102079

Commercial data

Packaging size	1
Net weight	1,950 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140070462
eCl@ss	27440214 D-Sub coupler