

UIC 558 18PIN SOCKET KIT-FC-AU



Part number	09 58 018 1013
Specification	UIC 558 18PIN SOCKET KIT-FC-AU
HARTING eCatalogue	https://b2b.harting.com/09580181013

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connector sets
Series of hoods/housings	HARTING UIC 558
Element	Connector sets

Version

Termination method	Crimp termination
Gender	Female
Number of contacts	18
Details	Crimp contacts enclosed separatly

Technical characteristics

Conductor cross-section	0.75 1 mm²
Conductor cross-section	AWG 18 AWG 17
Rated current	10 A
Rated voltage	60 V
Insulation resistance	>10 ⁷ Ω
Contact resistance	≤4 mΩ
Stripping length	5 mm
Tightening torque	5 Nm Fixing screws M6
Limiting temperature	-50 +125 °C
Mating cycles	≥10,000



Technical characteristics

Degree of protection acc. to IEC 60529	IP69K mated condition
Degree of protection acc. to IEC 60329	IP67 unmated condition & cover closed

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7035 (light grey) RAL 3020 (traffic red)
Material (seal)	Silicone
Material (locking)	Stainless steel
Material flammability class acc. to UL 94	V-0

Specifications and approvals

	UIC 50558 IRS 50558
Specifications	IEC 61373 Category 2
	IEC 60529

Commercial data

Packaging size	1
Net weight	589 g
Country of origin	India
European customs tariff number	85366990
GTIN	5713140190276
eCl@ss	27440102 Circular connector (for field assembly)