

## DSUB SV MA SSDP ANG36-254 37P PL3 GC M3



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 65 462 7815  |
| Specification      | DSUB SV MA SSDP ANG36-254 37P<br>PL3 GC M3  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09654627815">https://b2b.harting.com/09654627815</a> |

### Identification

|                            |                   |
|----------------------------|-------------------|
| Category                   | Connectors        |
| Series                     | D-Sub             |
| Identification             | Standard          |
| Element                    | Connector         |
| Specification              | Low-profile       |
| Description of the contact | Stamped<br>Angled |

### Version

|                    |                              |
|--------------------|------------------------------|
| Termination method | Wave soldering termination   |
| Gender             | Male                         |
| Size               | D-Sub 4                      |
| Connection type    | Motherboard to daughtercard  |
| Number of contacts | 37                           |
| further contacts   | With grounding pin           |
| Termination length | 2.9 mm                       |
| PCB fixing         | With board locks             |
| Locking type       | Fixing flange with thread M3 |

### Technical characteristics

|                                    |         |
|------------------------------------|---------|
| Distance between rows              | 2.54 mm |
| Contact spacing (termination side) | 2.76 mm |
| Rated current                      | 6.5 A   |



Pushing Performance  
 Since 1945

## Technical characteristics

|                                  |                           |
|----------------------------------|---------------------------|
| Clearance distance               | ≥1 mm                     |
| Creepage distance                | ≥1 mm                     |
| Insulation resistance            | >10 <sup>10</sup> Ω       |
| Contact resistance               | ≤10 mΩ                    |
| Tightening torque                | ≤0.6 Nm Female screw lock |
| Limiting temperature             | -55 ... +125 °C           |
| Insertion force                  | ≤123 N                    |
| Withdrawal force                 | ≥11 N<br>≤82 N            |
| Performance level                | 3                         |
| Mating cycles                    | ≥50                       |
| Test voltage U <sub>r,m.s.</sub> | 1 kV                      |
| Isolation group                  | IIIa (175 ≤ CTI < 400)    |
| PCB thickness                    | ≥1.6 mm                   |
| Installation height              | 3.6 mm                    |
| Hot plugging                     | No                        |

## Material properties

|   |   |
|---|---|
| Material (insert)                         | Thermoplastic resin, glass-fibre filled (PBTP)<br>Shell: Plated steel |
| Colour (insert)                           | Black   |
| Material (contacts)                       | Copper alloy  |
| Surface (contacts)                        | Noble metal over Ni   |
| Material flammability class acc. to UL 94 | V-0   |
| RoHS                                      | compliant   |
| ELV status                                | compliant   |
| China RoHS                                | e   |
| REACH Annex XVII substances               | Not contained   |
| REACH ANNEX XIV substances                | Not contained   |
| REACH SVHC substances                     | Not contained   |
| California Proposition 65 substances      | Yes   |
| California Proposition 65 substances      | Antimony trioxide<br>Lead<br>Nickel                                   |



**Pushing Performance**  
Since 1945

## Material properties

Requirement set with Hazard Levels R26

---

## Specifications and approvals

|                |                       |
|----------------|-----------------------|
| Specifications | DIN 41652             |
| UL / CSA       | UL 1977 ECBT2.E102079 |

---

## Commercial data

|                                |                        |
|--------------------------------|------------------------|
| Packaging size                 | 50                     |
| Net weight                     | 15 g                   |
| Country of origin              | Romania                |
| European customs tariff number | 85366990               |
| GTIN                           | 5713140079526          |
| eCl@ss                         | 27440214 D-Sub coupler |

---