

# D-SUB S 09P STR FE THR UNC PL2 GP RE



Part number	09 66 175 6582 741
Specification	D-SUB S 09P STR FE THR UNC PL2 GP RE
HARTING eCatalogue	https://b2b.harting.com/09661756582741

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	D-Sub
Identification	Standard
Element	Connector
Description of the contact	Stamped Straight

#### Version

Termination method	Reflow soldering termination (THR)
Gender	Female
Size	D-Sub 1
Connection type	Motherboard to daughtercard Mezzanine
Number of contacts	9
further contacts	With grounding pin
Termination length	2.1 mm
Locking type	Fixing flange with thread 4-40 UNC
Pack contents	200 pieces on reel

## **Technical characteristics**

Distance between rows	2.84 mm
Contact spacing (termination side)	2.74 mm
Rated current	8 A
Rated current	@ 40 °C

Page 1 / 3 | Creation date 2022-12-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



### **Technical characteristics**

Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤10 mΩ
Tightening torque	≤0.6 Nm Female screw lock
Limiting temperature	-55 +125 °C
Insertion force	≤30 N
Withdrawal force	≥3.3 N ≤20 N
Performance level	2 acc. to CECC 75301-802
Mating cycles	≥250
Test voltage U <sub>r.m.s.</sub>	1 kV
Isolation group	l (600 ≤ CTI)
PCB thickness	≥1.6 mm
Installation height	6.2 mm
Hot plugging	No
Moisture Sensitivity Level (MSL)	1 acc. to ECA/IPC/JEDEC J-STD-020D
Process Sensitivity Level (PSL)	R0 acc. to ECA/IPC/JEDEC J-STD-020D

## Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PPA) Shell: steel, nickel plated
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes



## Material properties

California Proposition 65 substances	Lead Nickel
Specifications and approvals	
Specifications	DIN 41652 CECC 75301-802
Commercial data	
Packaging size	1
Net weight	1.65 kg
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140218093
eCl@ss	27440214 D-Sub coupler

Page 3 / 3 | Creation date 2022-12-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany