




Pushing Performance  
Since 1945

## D-Sub 15P plast hood 1str-ent slo 4-40 s



Part number	09 67 015 0442 160
Specification	D-Sub 15P plast hood 1str-ent slo 4-40 s
HARTING eCatalogue	<a href="https://b2b.harting.com/09670150442160">https://b2b.harting.com/09670150442160</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	D-Sub
Type of hood/housing	Shell housing
Description of hood/housing	Cover can be screwed on

### Version

Size	D-Sub 2
Version	Top entry
Cable entry	1x
Cable fixing	Cable clamp
Locking type	With short locking screws Thread 4-40 UNC
2 parts	Yes
Separable	Yes

### Technical characteristics

Tightening torque	0.25 Nm Cable clamp screw
	0.25 Nm cover screw
	0.4 Nm Locking screw
Ambient temperature	-20 ... +90 °C
Degree of protection acc. to IEC 60529	IP30
Cable diameter	3.3 ... 8.5 mm

### Material properties

Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black



Pushing Performance  
Since 1945

## Material properties

Length	34.7 mm
Width	40 mm
Height	15.2 mm
RoHS	compliant with exemption
RoHS exemptions	6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight 6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	c3c36a64-4181-41a7-bdc6-2bc2fd6fd011
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Commercial data

Packaging size	100
Net weight	19.6 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140221277
eCl@ss	27440213 D-Sub hood