

# D SUB IP 67 09 POLE STRAIGHT FRONT PLAST



Part number	09 67 709 6715
Specification	D SUB IP 67 09 POLE STRAIGHT FRONT PLAST
HARTING eCatalogue	https://b2b.harting.com/09677096715

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	D-Sub
Identification	IP67
Element	Connector
Specification	With front frame
Description of the contact	Turned Straight

## Version

Termination method	Solder cup termination
Gender	Female
Size	D-Sub 1
Number of contacts	9
Locking type	Fixing flange with thread 4-40 UNC

## **Technical characteristics**

Conductor cross-section	0.5 mm <sup>2</sup>
Conductor cross-section	AWG 20
Rated current	5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	> 5 x 10 <sup>9</sup> Ω
Contact resistance	≤10 mΩ

Page 1 / 3 | Creation date 2022-09-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Technical characteristics

Tightening torque	0.4 0.6 Nm Screw
Limiting temperature	-25 +70 °C
Performance level	NM 30 (S4) 1
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67
Test voltage U <sub>r.m.s.</sub>	1.2 kV
Isolation group	Illa (175 ≤ CTI < 400)
Hot plugging	No

### Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled Shell: brass, tin plated
Colour (insert)	Red
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni
Layer thickness	≥0.76 µm
Layer thickness	≥30 µinch
Material (seal)	Silicone
Colour (seal)	Red
Material	Thermoplastic resin, glass-fibre filled
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	ecef7555-f643-4ceb-a337-fc54762297f1
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Page 2 / 3 | Creation date 2022-09-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079
Commercial data	
Packaging size	50
Net weight	11.24 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140095199
eCl@ss	27440214 D-Sub coupler