

# D-Sub male solder cup 9-pole IP 67



Part number	09 67 809 9615
Specification	D-Sub male solder cup 9-pole IP 67
HARTING eCatalogue	https://b2b.harting.com/09678099615

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	D-Sub
Identification	IP67
Element	Connector
Specification	With front frame
Description of the contact	Turned Straight

#### Version

Termination method	Solder cup termination
Gender	Male
Size	D-Sub 1
Number of contacts	9
Locking type	Fixing flange with thread M3

#### Technical characteristics

Conductor cross-section	0.5 mm²
Conductor cross-section	AWG 20
Rated current	5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	> 5 x 10 <sup>9</sup> Ω
Contact resistance	≤10 mΩ



## Technical characteristics

Tightening torque	0.4 0.6 Nm Screw
Limiting temperature	-25 +70 °C
Performance level	NM 30 (S4) 1
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67
Test voltage U <sub>r.m.s.</sub>	1.2 kV
Isolation group	IIIa (175 ≤ CTI < 400)
Hot plugging	No

# Material properties

Material properties	
Material (insert)	Thermoplastic resin, glass-fibre filled Shell: brass, tin plated
Colour (insert)	Red
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni
Layer thickness	≥0.76 µm
Layer thickness	≥30 µinch
Material (seal)	Silicone
Colour (seal)	Red
Material	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
	Compilant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
RoHS exemptions ELV status	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption
RoHS exemptions  ELV status  China RoHS	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances  REACH SVHC substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes  Lead
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances  REACH SVHC substances  ECHA SCIP number	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes  Lead  ecef7555-f643-4ceb-a337-fc54762297f1



# Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

## Commercial data

Packaging size	50
Net weight	25.28 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140095342
eCl@ss	27440214 D-Sub coupler