

09 67 837 8715

FRONT METAL

D SUB IP 67 37 POLE STRAIGHT

https://b2b.harting.com/09678378715

# D SUB IP 67 37 POLE STRAIGHT FRONT METAL



13.30	A Thirty			
32				
1		(1)		
			1 200	- madelling

Part number

Specification

HARTING eCatalogue

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	D-Sub
Identification	IP67
Element	Connector
Specification	With front frame
Description of the contact	Turned Straight

#### Version

Termination method	Solder cup termination
Gender	Female
Size	D-Sub 4
Number of contacts	37
Locking type	Fixing flange with thread M3

#### Technical characteristics

Conductor cross-section	0.5 mm²
Conductor cross-section	AWG 20
Rated current	5 A
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	$> 5 \times 10^9 \Omega$
Contact resistance	≤10 mΩ



## Technical characteristics

Tightening torque	0.4 0.6 Nm Screw
Limiting temperature	-25 +70 °C
Performance level	NM 30 (S4) 1
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67
Test voltage U <sub>r.m.s.</sub>	1.2 kV
Isolation group	IIIa (175 ≤ CTI < 400)
Hot plugging	No

# Material properties

Material Proportion			
Material (insert)	Thermoplastic resin, glass-fibre filled Shell: brass, tin plated		
Colour (insert)	Red		
Material (contacts)	Copper alloy		
Surface (contacts)	Noble metal over Ni		
Layer thickness	≥0.76 µm		
Layer thickness	≥30 µinch		
Material (seal)	Silicone		
Colour (seal)	Red		
Material	Zinc die-cast, nickel-plated		
Material flammability class acc. to UL 94	V-0		
RoHS	compliant with exemption		
	Compilant with exemption		
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight		
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight		
RoHS exemptions ELV status	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption		
RoHS exemptions  ELV status  China RoHS	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption		
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained		
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained		
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes		
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances  REACH SVHC substances	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes  Lead		
RoHS exemptions  ELV status  China RoHS  REACH Annex XVII substances  REACH ANNEX XIV substances  REACH SVHC substances  REACH SVHC substances  ECHA SCIP number	6(c): Copper alloy containing up to 4 % lead by weight compliant with exemption  50  Not contained  Not contained  Yes  Lead  ecef7555-f643-4ceb-a337-fc54762297f1		



# Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

## Commercial data

Packaging size	25
Net weight	48.32 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140095458
eCl@ss	27440214 D-Sub coupler