

D SUB IP 67 50 POLE STRAIGHT FRONT METAL



| Specification | D SUB IP 67 50 POLE STRAIGHT FRONT METAL |
|--------------------|---|
| HARTING eCatalogue | https://b2b.harting.com/09678507615 |

09 67 850 7615

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|--------------------|
| Series | D-Sub |
| Identification | IP67 |
| Element | Connector |
| Specification | With front frame |
| Description of the contact | Turned Straight |

Part number

Version

| Termination method | Solder cup termination |
|--------------------|------------------------------------|
| Gender | Male |
| Size | D-Sub 5 |
| Number of contacts | 50 |
| Locking type | Fixing flange with thread 4-40 UNC |

Technical characteristics

| Conductor cross-section | 0.5 mm² |
|-------------------------|-------------------------|
| Conductor cross-section | AWG 20 |
| Rated current | 5 A |
| Clearance distance | ≥1 mm |
| Creepage distance | ≥1 mm |
| Insulation resistance | > 5 x 10 ⁹ Ω |
| Contact resistance | ≤10 mΩ |



Technical characteristics

| Tightening torque | 0.4 0.6 Nm Screw |
|--|------------------------|
| Limiting temperature | -25 +70 °C |
| Performance level | NM 30 (S4) 1 |
| Mating cycles | ≥500 |
| Degree of protection acc. to IEC 60529 | IP67 |
| Test voltage U _{r.m.s.} | 1.2 kV |
| Isolation group | IIIa (175 ≤ CTI < 400) |
| Hot plugging | No |

Material properties

| Material properties | |
|---|---|
| Material (insert) | Thermoplastic resin, glass-fibre filled Shell: brass, tin plated |
| Colour (insert) | Red |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Layer thickness | ≥0.76 µm |
| Layer thickness | ≥30 µinch |
| Material (seal) | Silicone |
| Colour (seal) | Red |
| Material | Zinc die-cast, nickel-plated |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| | |
| ELV status | compliant with exemption |
| ELV status China RoHS | compliant with exemption 50 |
| | |
| China RoHS | 50 |
| China RoHS REACH Annex XVII substances | 50 Not contained |
| China RoHS REACH Annex XVII substances REACH ANNEX XIV substances | Not contained Not contained |
| China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances | Not contained Not contained Yes |
| China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances REACH SVHC substances | Not contained Not contained Yes Lead |
| China RoHS REACH Annex XVII substances REACH ANNEX XIV substances REACH SVHC substances REACH SVHC substances ECHA SCIP number | Not contained Not contained Yes Lead ecef7555-f643-4ceb-a337-fc54762297f1 |



Specifications and approvals

| Specifications | DIN 41652 |
|----------------|-----------------------|
| UL / CSA | UL 1977 ECBT2.E102079 |

Commercial data

| Packaging size | 25 |
|--------------------------------|------------------------|
| Net weight | 48.16 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140095489 |
| eCl@ss | 27440214 D-Sub coupler |