

Han Yellock multiplier 4:1



| Part number | 11 05 105 2804 |
|--------------------|-------------------------------------|
| Specification | Han Yellock multiplier 4:1 |
| HARTING eCatalogue | https://b2b.harting.com/11051052804 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Inserts |
|---------------|---|
| Series | Han-Yellock [®] |
| Element | Multiplier |
| Specification | 4 Bridged contacts 1 Unbridged contacts |

Version

| Gender | Female |
|--------------------|--------|
| Number of contacts | 5 |

Technical characteristics

| Insulation resistance | >10 ¹⁰ Ω |
|-----------------------|---------------------|
| Limiting temperature | -40 +125 °C |
| Mating cycles | ≥500 |

Material properties

| Material (insert) | Polycarbonate (PC) |
|---|--|
| Colour (insert) | RAL 3000 (flame red) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Material properties

| REACH Annex XVII substances | Not contained |
|--------------------------------------|--------------------------------------|
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 5dbb3851-b94e-4e88-97a1-571845975242 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| Specifications | IEC 60664-1 IEC 61984 |
|----------------|--------------------------|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|---|
| Net weight | 7.1 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140109704 |
| eCl@ss | 27440205 Contact insert for industrial connectors |