



Pushing Performance
Since 1945

Han 16B-SCP-HTE2-HC-f. DL-M25



Part number	19 30 916 0466
Specification	Han 16B-SCP-HTE2-HC-f. DL-M25
HARTING eCatalogue	https://b2b.harting.com/19309160466

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Hood
Description of hood/housing	Corrosion resistant
Type	High construction

Version

Size	16 B
Version	Top entry
Cable entry	2x M25
Locking type	Double locking lever
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66 IP67
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
-------------------------	--------------------



Pushing Performance
Since 1945

Material properties

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	1
Net weight	219 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140164741
eCl@ss	27440202 Shell for industrial connectors