

## Han-Eco 16B-HSM2-for DL-M40 with cover



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 43 016 0268  |
| Specification      | Han-Eco 16B-HSM2-for DL-M40 with cover  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19430160268">https://b2b.harting.com/19430160268</a> |

### Identification

|                             |                           |
|-----------------------------|---------------------------|
| Category                    | Hoods/Housings            |
| Series of hoods/housings    | Han-Eco® B                |
| Type of hood/housing        | Surface mounted housing   |
| Description of hood/housing | With thermo-plastic cover |

### Version

|              |                                    |
|--------------|------------------------------------|
| Size         | 16 B                               |
| Version      | Side entry                         |
| Cable entry  | 2x M40                             |
| Locking type | Double locking lever (on the hood) |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Number of relockings                   | ≥500   |
| Degree of protection acc. to IEC 60529 | IP66   |

### Material properties

|                         |  |
|-------------------------|--|
| Material (hood/housing) | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)   | RAL 9005 (jet black)                     |
| Material (seal)         | NBR                                      |
| Colour (seal)           | RAL 9005 (jet black)                     |



Pushing Performance  
Since 1945

## Material properties

|   |  |
|---|--|
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant                                    |
| ELV status                                | compliant                                    |
| China RoHS                                | e  |
| REACH Annex XVII substances               | Not contained                                |
| REACH ANNEX XIV substances                | Not contained                                |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Naphthalene                                  |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                         |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                 |

## Specifications and approvals

|                |   |
|----------------|---|
| Specifications | IEC 61984<br>EN 45545-2 Fire protection on railway vehicles |
| CE             | Yes   |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140179332                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |