

M8-Screw-4P-M-ANG



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 02 359 3401 |
| Specification | M8-Screw-4P-M-ANG |
| HARTING eCatalogue | https://b2b.harting.com/21023593401 |

Identification

| | |
|---------------|------------------------|
| Category | Connectors |
| Series | Circular connectors M8 |
| Element | Cable connector |
| Specification | Angled |

Version

| | |
|--------------------|-------------------|
| Termination method | Screw termination |
| Gender | Male |
| Shielding | Unshielded |
| Number of contacts | 4 |
| Coding | A-coding |
| Locking type | Screw locking |

Technical characteristics

| | |
|-------------------------|------------------------------|
| Conductor cross-section | 0.09 ... 0.5 mm ² |
| Conductor cross-section | AWG 28 ... AWG 20 |
| Rated current | 4 A |
| Rated voltage | 30 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---|-----------------------|
| Tightening torque | 0.4 Nm |
| Wrench size (knurled screw / knurled nut) | 13 |
| Limiting temperature | -30 ... +85 °C |
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP67 locked condition |
| Cable diameter | 4 ... 5.5 mm |
| Isolation group | I (600 ≤ CTI) |

Material properties

| | |
|--------------------------------------|--|
| Material (insert) | Polyamide (PA) |
| Material (contacts) | Brass |
| Surface (contacts) | Au over Ni Mating side |
| Material (hood/housing) | Polyamide (PA) Copper-zinc alloy |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |

Specifications and approvals

| | |
|----------------|---|
| Specifications | IEC 61076-2-104 |
| UL / CSA | UL 2238 CYJV.E302521 CSA-C22.2 No. 182.3 CYJV7.E302521 |

Commercial data

| | |
|-------------------|---------|
| Packaging size | 1 |
| Net weight | 18.4 g |
| Country of origin | Czechia |



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|--|
| European customs tariff number | 85366990 |
| GTIN | 5713140224889 |
| eCl@ss | 27440116 Circular connector (for field assembly) |
