

## M12-P-ACC-HOUSING M FRONT MOUNTING



Image is for illustration purposes only. Please refer to product description.

Part number	21 03 302 1001 407
Specification	M12-P-ACC-HOUSING M FRONT MOUNTING
HARTING eCatalogue	<a href="https://b2b.harting.com/21033021001407">https://b2b.harting.com/21033021001407</a>

### Identification

Category	Accessories
Series	Circular connectors M12
Type of accessory	Housing
Description of the accessory	for front mounting

### Version

Gender	Male
Locking type	Screw locking PushPull

### Technical characteristics

Tightening torque	2 Nm Lock nut
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition

### Material properties

Material (seal)	NBR
Colour (seal)	Grey
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	IEC 61076-2-010
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079

## Commercial data

Packaging size	30
Net weight	12 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140236387
eCl@ss	27440292 Connector component (accessories)