

PCB receptacle female front A-cod 5-pole



Part number	21 03 321 2531
Specification	PCB receptacle female front A-cod 5-pole
HARTING eCatalogue	https://b2b.harting.com/21033212531

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connectors
Series	Circular connectors M12
Identification	PushPull
Element	PCB adapter
Specification	Straight
	incl. housing
	for front mounting

Version

Termination method	Reflow soldering termination (THR)
Gender	Female
Shielding	Shielded
Number of contacts	5
Coding	A-coding
Locking type	Screw locking PushPull

Technical characteristics

Rated current	4 A
Rated voltage	60 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 ⁸ Ω



Technical characteristics

Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut
Limiting temperature	-40 +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP65 / IP67 mated condition
Isolation group	I (600 ≤ CTI)

Material properties

Liquid crystal polymer (LCP)
Copper alloy
Au over Ni Mating side
Zinc die-cast
V-0
compliant with exemption
6(c): Copper alloy containing up to 4 % lead by weight
compliant with exemption
50
Not contained
Not contained
Yes
6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead
0d7d3693-d625-47ab-934a-d241bf72c86e
Yes
Lead Nickel Naphthalene
EN 45545-2 (2020-08)
R26

Specifications and approvals

Specifications	IEC 61076-2-101
UL / CSA	UL 1977 ECBT2.E102079
	CSA-C22.2 No. 182.3 ECBT8.E102079



Commercial data

Packaging size	1
Net weight	25.25 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140137790
eCl@ss	27460201 PCB connector (board connector)