

M12 X-cod st/st m/m PUR Grey 10m



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 33 050 5806 100 |
| Specification | M12 X-cod st/st m/m PUR Grey 10m |
| HARTING eCatalogue | https://b2b.harting.com/21330505806100 |

Identification

| | |
|---------------|---|
| Category | System cabling |
| Series | Circular connectors M12 |
| Element | Cable assemblies |
| Specification | Pre-assembled on both sides |
| Connector 1 | M12 X-coding Male Straight Press&Go |
| Connector 2 | M12 X-coding Male Straight Press&Go |
| Type of cable | Copper cable (round) |

Version

| | |
|-----------------|----------------|
| Cable length | 10 m |
| Number of cores | 8 |
| Core structure | 4x 2x AWG 26/7 |
| Shielding | Shielded |
| Coding | X-coding |

Technical characteristics

| | |
|------------------------------|--|
| Transmission characteristics | Cat. 6 _A Class E _A up to 500 MHz |
|------------------------------|--|



Pushing Performance
Since 1945

Technical characteristics

| | |
|----------------------|------------------------|
| Data rate | 10 Mbit/s |
| | 100 Mbit/s |
| | 1 Gbit/s |
| | 2.5 Gbit/s |
| | 5 Gbit/s |
| | 10 Gbit/s |
| Limiting temperature | -40 ... +80 °C moved |
| | -40 ... +80 °C unmoved |
| Cable diameter | 6.7 mm ± 0.3 mm |

Material properties

| | |
|------------------|--------------------|
| Material (cable) | PUR (polyurethane) |
| Colour (cable) | Grey |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Country of origin | Romania |
| European customs tariff number | 85444290 |
| GTIN | 5713140248823 |
| eCl@ss | 27060390 Ready-made data cable (unspecified) |