

## M12 X-coded Cable Assembly 9,5 m




Image is for illustration purposes only. Please refer to product description.

Part number	21 33 050 5810 095
Specification	M12 X-coded Cable Assembly 9,5 m
HARTING eCatalogue	<a href="https://b2b.harting.com/21330505810095">https://b2b.harting.com/21330505810095</a>

### Identification

Category	System cabling
Series	Circular connectors M12
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	M12 X-coding Male Straight Press&Go
Connector 2	M12 X-coding Male Straight Press&Go
Type of cable	Copper cable (round)

### Version

Cable length	9.5 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Shielding	Shielded
Coding	X-coding

### Technical characteristics

Transmission characteristics	Cat. 6 <sub>A</sub> Class E <sub>A</sub> up to 500 MHz
------------------------------	--



**Pushing Performance**  
Since 1945

## Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
	10 Gbit/s
Limiting temperature	-40 ... +80 °C moved
	-40 ... +80 °C unmoved
Cable diameter	6.7 mm ± 0.3 mm

## Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Yellow

## Commercial data

Packaging size	1
Net weight	540.24 g
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140248724
eCl@ss	27060390 Ready-made data cable (unspecified)