

## M23\_19P MA,Int-thread,ANG PUR cable,10M



Image is for illustration purposes only. Please refer to product description.

Part number	21 37 340 0D74 100
Specification	M23_19P MA,Int-thread,ANG PUR cable,10M
HARTING eCatalogue	<a href="https://b2b.harting.com/21373400D74100">https://b2b.harting.com/21373400D74100</a>

### Identification

Category	System cabling
Series	Circular connectors M23
Identification	Signal
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	M23 Male Angled
Type of cable	Copper cable (round)
Features	Flame retardancy Oil and UV resistant Highly EMC resistant Halogen freeness

### Version

Cable length	10 m
Number of cores	19
Core structure	3x AWG 18 + 16x AWG 22

### Technical characteristics

Rated voltage	150 V
Rated current (signal)	2 A
Rated current (power)	9 A
Limiting temperature	-40 ... +80 °C



**Pushing Performance**  
Since 1945

## Technical characteristics

Degree of protection acc. to IEC 60529	IP67
--	------

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (cable)	PUR (polyurethane)
Colour (cable)	Black
Material (overmoulding)	Thermoplastic polyurethane (TPU)
Colour (overmoulding)	Black

## Commercial data

Packaging size	1
Country of origin	China
European customs tariff number	85444290
GTIN	5713140241077
eCl@ss	27060311 Assembled sensor actuator-line