

M23_19P FE,Int-thread,ANG PVC cable,10M



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 37 360 0D75 100 |
| Specification | M23_19P FE,Int-thread,ANG PVC cable,10M |
| HARTING eCatalogue | https://b2b.harting.com/21373600D75100 |

Identification

| | |
|----------------|--|
| Category | System cabling |
| Series | Circular connectors M23 |
| Identification | Signal |
| Element | Cable assemblies |
| Specification | Pre-assembled on one side |
| Connector 1 | M23 Female Angled |
| Type of cable | Copper cable (round) |
| Features | Flame retardancy Oil and UV resistant Highly EMC resistant |

Version

| | |
|-----------------|------------------------|
| Cable length | 10 m |
| Number of cores | 19 |
| Core structure | 3x AWG 18 + 16x AWG 22 |

Technical characteristics

| | |
|--|----------------|
| Rated voltage | 150 V |
| Rated current (signal) | 2 A |
| Rated current (power) | 9 A |
| Limiting temperature | -40 ... +80 °C |
| Degree of protection acc. to IEC 60529 | IP67 |



Pushing Performance
Since 1945

Material properties

| | |
|-------------------------|----------------------------------|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Silver plated |
| Material (cable) | PVC |
| Colour (cable) | Black |
| Material (overmoulding) | Thermoplastic polyurethane (TPU) |
| Colour (overmoulding) | Black |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Country of origin | China |
| European customs tariff number | 85444290 |
| GTIN | 5713140241336 |
| eCl@ss | 27060311 Assembled sensor actuator-line |