

## M12-ADPT-M12/M12-5/4P-ACOD-M/F/F-STR



Image is for illustration purposes only. Please refer to product description.

Part number	21 43 311 9500
Specification	M12-ADPT-M12/M12-5/4P-ACOD-M/F/F-STR
HARTING eCatalogue	<a href="https://b2b.harting.com/21433119500">https://b2b.harting.com/21433119500</a>

### Identification

Category	Accessories
Series	Circular connectors M12
Connector 1	Male
Connector 2	Female
Type of accessory	T-splitter

### Version

Gender	Male Female
Shielding	Unshielded
Number of contacts	4 5
Coding	A-coding

### Technical characteristics

Rated current	4 A
Rated voltage	60 V AC/DC
Rated impulse voltage	1.5 kV
Limiting temperature	-25 ... +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP67

### Material properties

Material (contacts)	Copper alloy
---------------------	--------------



**Pushing Performance**  
Since 1945

## Material properties

Surface (contacts) Au over Ni Mating side

Material flammability class acc. to UL 94 V-0

## Specifications and approvals

Specifications IEC 61076-2-101

## Commercial data

Packaging size 1

Country of origin Germany

European customs tariff number 85366990

GTIN 5713140236653

eCl@ss 27440292 Connector component (accessories)