

## Ha-VIS eCon 2050B-A



Image is for illustration purposes only. Please refer to product description.

Part number	24 02 005 0010
Specification	Ha-VIS eCon 2050B-A
HARTING eCatalogue	<a href="https://b2b.harting.com/24020050010">https://b2b.harting.com/24020050010</a>

### Identification

Series	Ha-VIS eCon 2000
Element	Industrial Ethernet Switches
Specification	Unmanaged
Type of Ethernet	Fast Ethernet

### Version

Total number of ports	5
Fixing	35 mm DIN rail acc. to EN 60715
Switching technology	Store and Forward
Frame size	1.5 kB
MAC table size	1k Entries
Packet buffer size	0.44 Megabit
Non blocking	Yes
Quality of service	Yes
Energie Efficient Ethernet	Yes
Flow control	Off
Signal contact	No
Pack contents	Pluggable screw contact for power supply Assembly instructions

### Termination data

Nominal voltage	24 V DC 48 V DC
Permissible voltage	9 ... 60 V DC



Pushing Performance  
 Since 1945

## Termination data

Surge protection	Yes
Operating current	<42 mA @ 24 V DC <23 mA @ 48 V DC
Supply circuit	SELV (Circuit Breaker 10 A)
Starting current	<2.8 A @ 24 V DC <5.6 A @ 48 V DC
Overcurrent protection	2 A At input
Power consumption	<1.01 W @ 24 V DC
Termination method	Pluggable screw contact
Number of contacts	3
Conductor cross-section	0.08 ... 2.5 mm <sup>2</sup>
Conductor cross-section	AWG 28 ... AWG 12
Pinout	+ / - / FE
Reverse polarity proof	Yes

## Technical characteristics

Operating temperature	0 ... +55 °C
Storage temperature	-40 ... +85 °C
Relative humidity	0 ... 95 % Non-condensing (operation) 0 ... 95 % Non-condensing (storage/transport)
Air pressure	≥795 hPa ≈ 2000 m
Degree of protection acc. to IEC 60529	IP30 mated condition
MTBF	≈2,860,000 h

## Ethernet ports copper

10/100 Mbit/s (RJ45-Ports)	5
Fast-Ethernet Ports 10/100 Mbit/s (RJ45-Ports) Transmission standards: 10BASE-T, 100BASE-TX Transmission physics: Twisted Pair Cat. 5 Transmission length: 100 m Data rate: 10/100 Mbit/s Auto-negotiation: yes Auto-polarity: yes Auto-MDI(X): yes	5
Transmission standard	10BASE-Te 100BASE-TX EEE
Auto-negotiation	Yes
Auto-polarity	Yes



**Pushing Performance**  
 Since 1945

## Ethernet ports copper

Auto-MDI(X)	Yes
Transmission physics	Twisted Pair Cat. 5
Data rate	10 Mbit/s 100 Mbit/s
Transmission length	100 m

## Material properties

Material (hood/housing)	Aluminium (anodised)
Length	27.3 mm
Width	46.5 mm
Height	113.5 mm
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes

## Specifications and approvals

Specifications	EN 55022 Radio disturbance characteristics
	EN 61000-4-2 Electrostatic discharge (ESD)
	EN 61000-4-3 Electromagnetic field
	EN 61000-4-4 Rapid transients (burst)
	EN 61000-4-5 Surge voltages
	EN 61000-4-6 conducted disturbances
	EN 61000-6-4 emission standard
	IEC 60068-2-6 Vibration (sinusoidal)
	IEEE 802.3
Approvals	DNV GL
UL / CSA	UL 508 NRAQ.E253944
	CSA-C22.2 No. 142 NRAQ7.E253944
PROFINET	Yes
EtherNet/IP	Yes
CE	Yes
FCC	Yes



**Pushing Performance**  
Since 1945

## Commercial data

Packaging size	1
Net weight	202.9 g
Country of origin	Germany
European customs tariff number	85176200
GTIN	5713140147188
eCl@ss	19170130 Network switch (general application)