

Han F+B CA 17D 0,5mm² f/- st/- PUR 7,5m



Image is for illustration purposes only. Please refer to product description.

Part number	33 50 420 0306 075
Specification	Han F+B CA 17D 0,5mm ² f/- st/- PUR 7,5m
HARTING eCatalogue	https://b2b.harting.com/33504200306075

Identification

Category	System cabling
Series	Han [®] F+B
Element	Cable assemblies
Specification	Pre-assembled on one side
Connector 1	Female Hood
Type of cable	Copper cable (round)

Version

Cable length	7.5 m
Number of cores	17
Core structure	0.5 mm ²
Number of contacts	17
PE contact	Yes

Technical characteristics

Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Limiting temperature	-20 ... +80 °C moved -40 ... +80 °C unmoved
Degree of protection acc. to IEC 60529	IP69



Pushing Performance
Since 1945

Technical characteristics

Minimum bending radius	10x Cable diameter (repeated bending)
	5x Cable diameter (singular bending)

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Grey

Specifications and approvals

Specifications	EN 50525-1
	IEC 60228
	EN 50363-3
	EN 50363-10-2
Approvals	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topactive OKTO
	Ecolab Topax 66
	Ecolab Topax 990

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140238213
eCl@ss	27060311 Assembled sensor actuator-line