

Han 1A CA M12-X-cod. +latch m/m PVC 1m




Image is for illustration purposes only. Please refer to product description.

Part number	33 50 525 2808 010
Specification	Han 1A CA M12-X-cod. +latch m/m PVC 1m
HARTING eCatalogue	https://b2b.harting.com/33505252808010

Identification

Category	System cabling
Series	Han [®] 1A
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	Han [®] 1A
Connector 2	Han [®] 1A

Version

Cable length	1 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Coding	X-coding
Locking type	Snap-in latches

Technical characteristics

Transmission characteristics	Cat. 6A Class E _A up to 500 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
Limiting temperature	-20 ... +80 °C unmoved
	-20 ... +80 °C moved



Pushing Performance
Since 1945

Material properties

Material (cable)	PVC
Colour (cable)	Yellow
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Specifications and approvals

Specifications	EN 50173-1 IEC 60332-1-2
----------------	-----------------------------

Commercial data

Packaging size	1
Country of origin	Romania
European customs tariff number	85444290
GTIN	5713140244290
eCl@ss	27060311 Assembled sensor actuator-line