



Pushing Performance  
Since 1945

## PP FO CABL-40M-2xPP Metal LCD OV MM62,5



|                    |   |
|--------------------|---|
| Part number        | 33 58 231 0400 028  |
| Specification      | PP FO CABL-40M-2xPP Metal LCD OV MM62,5   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/33582310400028">https://b2b.harting.com/33582310400028</a> |

### Identification

|               |                             |
|---------------|-----------------------------|
| Category      | System cabling              |
| Series        | HARTING PushPull (V4)       |
| Element       | Cable assemblies            |
| Specification | Pre-assembled on both sides |
| Connector 1   | HARTING PushPull (V4)       |
| Connector 2   | HARTING PushPull (V4)       |
| Type of cable | FO cable                    |

### Version

|                |               |
|----------------|---------------|
| Cable length   | 40 m          |
| Core structure | 62.5 / 125 µm |

### Technical characteristics

|  |                |
|--|----------------|
| Limiting temperature                   | -40 ... +70 °C |
| Degree of protection acc. to IEC 60529 | IP65 / IP67    |
| Cable diameter                         | 7 mm           |

### Material properties

|                         |  |
|-------------------------|--|
| Material (hood/housing) | Metal  |
| Material (cable)        | PUR (polyurethane)   |
| RoHS                    | compliant with exemption   |
| RoHS exemptions         | 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight |
| ELV status              | compliant with exemption   |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |  |
|--------------------------------------|--|
| China RoHS                           | 50   |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol<br>Lead |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Antimony trioxide<br>Lead<br>Nickel<br>Naphthalene   |

## Specifications and approvals

|                |                                |
|----------------|--------------------------------|
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|--------------------------------|

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 104 g  |
| Country of origin              | Czechia                                      |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140153745                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |