

Han-Port Combi insert D/HIFF breakout



Part number	39 50 001 0450
Specification	Han-Port Combi insert D/HIFF breakout
HARTING eCatalogue	https://b2b.harting.com/39500010450

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Sockets
Series of hoods/housings	Han-Port [®]
Element	Socket
Specification	2 cut-outs for HIFF data module
N7 ·	
Version	
Termination method	Spring clamp termination
Field of application	Germany (VDE)
Termination data	
Supply voltage	250 V AC
Nominal current	16 A
Nominal frequency	50 Hz
Technical characteristics	
Conductor cross-section	2.5 mm ²
Mounting depth	43 mm
Material properties	
Material (hood/housing)	Thermoplastic
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2022-12-29 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Commercial data

Packaging size	1
Net weight	80 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140190467
eCl@ss	27144042 Plug socket