

## Han-Port Combi insert CHN/2 HIFF module



	Part number	39 50 012 0458
	Specification	Han-Port Combi insert CHN/2 HIFF module
	HARTING eCatalogue	https://b2b.harting.com/39500120458

Image is for illustration purposes only. Please refer to product description.

## Identification

<b>0</b> /			
Category	Sockets		
Series of hoods/housings	Han-Port <sup>®</sup>		
Element	Socket		
Version			
Termination method	Screw termination		
Field of application	China		
Details	1x RJ45 Cat.6 / 1x USB-A 3.0, enclosed separatly		
Termination data			
Supply voltage	250 V AC		
Nominal current	10 A		
Nominal frequency	50 Hz		
Technical characteristics			
Conductor cross-section	4 mm <sup>2</sup>		
Mounting depth	43 mm		
Material properties			
Material (hood/housing)	Thermoplastic		
RoHS	compliant		
ELV status	compliant		
China RoHS	e		

Page 1 / 2 | Creation date 2023-01-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany



## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Commercial data

Packaging size	1
Net weight	125.44 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140190443
eCl@ss	27144042 Plug socket