




Pushing Performance
Since 1945

InduCom 15p T&S-entry hexscrew 4-40



| | |
|--------------------|---|
| Part number | 61 03 001 2016 160 |
| Specification | InduCom 15p T&S-entry hexscrew 4-40 |
| HARTING eCatalogue | https://b2b.harting.com/61030012016160 |

Identification

| | |
|-----------------------------|---------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | D-Sub InduCom |
| Type of hood/housing | Shell housing |
| Description of hood/housing | With internal earth |

Version

| | |
|-------------------|---|
| Size | D-Sub 2 |
| Cable entry | 1x |
| Strain relief | An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable. |
| Locking type | Hexagonal screw with captive washer Thread 4-40 UNC |
| ground connection | With internal grounding block |
| 2 parts | Yes |
| Separable | Yes |

Technical characteristics

| | |
|--|--------------------------|
| Tightening torque | 0.4 Nm ground connection |
| | 0.4 Nm cover screw |
| | 0.4 Nm Locking screw |
| Ambient temperature | -55 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP30 |

Material properties

| | |
|-------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast |
| Material (screw) | Steel, nickel plated |



Pushing Performance
Since 1945

Material properties

| | |
|--------|---------|
| Length | 36.4 mm |
| Width | 39.5 mm |
| Height | 14.8 mm |

Commercial data

| | |
|--------------------------------|---------------------|
| Packaging size | 1 |
| Net weight | 44.6 g |
| Country of origin | China |
| European customs tariff number | 85366990 |
| GTIN | 5713140222519 |
| eCl@ss | 27440213 D-Sub hood |