



## InduCom9 MVB/WTB female PL2 UNC set



|                    |   |
|--------------------|---|
| Part number        | 66 63 009 6028  |
| Specification      | InduCom9 MVB/WTB female PL2 UNC set   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/66630096028">https://b2b.harting.com/66630096028</a> |

### Identification

|               |                   |
|---------------|-------------------|
| Category      | Connectors        |
| Series        | D-Sub             |
| Element       | Bus interface     |
| Specification | MVB/WTB interface |

### Version

|                    |  |
|--------------------|--|
| Termination method | Cage-clamp termination                       |
| Gender             | Female                                       |
| Size               | D-Sub 1                                      |
| Number of contacts | 9  |
| Version            | Top entry                                    |
| Cable entry        | 2x   |
| Locking type       | Hexagonal screw Thread 4-40 UNC              |
| Pack contents      | Blind plate<br>Crimp flange<br>Crimp ferrule |

### Technical characteristics

|                         |  |
|-------------------------|--|
| Conductor cross-section | 0.08 ... 0.5 mm <sup>2</sup>                 |
| Conductor cross-section | AWG 28 ... AWG 20                            |
| Rated voltage           | <50 V AC<br><75 V DC                         |
| Stripping length        | 5 ... 6 mm                                   |
| Tightening torque       | ≤0.4 Nm Locking screw<br>≤0.3 Nm cover screw |



Pushing Performance  
Since 1945

## Technical characteristics

|  |                |
|--|----------------|
| Limiting temperature                   | -40 ... +70 °C |
| Performance level                      | 2              |
| Mating cycles                          | ≥250           |
| Degree of protection acc. to IEC 60529 | IP40           |
| Test voltage $U_{r.m.s.}$              | 0.5 kV         |

## Material properties

|                                      |  |
|--------------------------------------|--|
| Material (insert)                    | Thermoplastic resin, glass-fibre filled                |
| Material (contacts)                  | Copper alloy   |
| Surface (contacts)                   | Noble metal over Ni                                    |
| Material (hood/housing)              | Zinc die-cast  |
| Length                               | 61.7 mm  |
| Width                                | 31.6 mm  |
| Height                               | 14.8 mm  |
| RoHS                                 | compliant with exemption                               |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50   |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Yes  |
| REACH SVHC substances                | Lead   |
| ECHA SCIP number                     | 5f2b96e8-feaf-4131-b3cd-8b723c130d93                   |
| California Proposition 65 substances | Yes  |
| California Proposition 65 substances | Antimony trioxide<br>Lead<br>Nickel                    |

## Commercial data

|                                |               |
|--------------------------------|---------------|
| Packaging size                 | 10            |
| Net weight                     | 82.32 g       |
| Country of origin              | China         |
| European customs tariff number | 85366990      |
| GTIN                           | 5713140216587 |



**Pushing Performance**  
Since 1945

## Commercial data

eCl@ss

27440302 D-Sub-Connector

---