




Pushing Performance  
Since 1945

## InduCom 9P top entry PCB hood w 4-40UNC



Part number	66 67 009 0346 160
Specification	InduCom 9P top entry PCB hood w 4-40UNC
HARTING eCatalogue	<a href="https://b2b.harting.com/66670090346160">https://b2b.harting.com/66670090346160</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	D-Sub InduCom
Type of hood/housing	Shell housing
Description of hood/housing	Suitable for circuit boards

### Version

Size	D-Sub 1
Version	Top entry
Cable entry	2x
Strain relief	An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable.
Locking type	Hexagonal screw Thread 4-40 UNC
2 parts	Yes
Separable	Yes

### Technical characteristics

Tightening torque	0.4 Nm cover screw
	0.4 Nm Locking screw
Ambient temperature	-20 ... +90 °C
Degree of protection acc. to IEC 60529	IP30

### Material properties

Material (hood/housing)	Zinc die-cast
Material (screw)	Brass, nickel plated
Length	63.4 mm



**Pushing Performance**  
Since 1945

## Material properties

Width	31 mm
Height	14.8 mm

## Commercial data

Packaging size	10
Country of origin	China
European customs tariff number	85366990
GTIN	5713140222304
eCl@ss	27440213 D-Sub hood